

Canon

73 S Riverside DR, STE 300
Elgin, IL 60120-6425
Phone: 847.760.9282
Fax: 847.760.9281

LANgrafiX

sales@langrafix.net
www.langrafix.com

ColorPASS-Z70

achieve extraordinary
color printing
capabilities

productivity

speed

flexibility

accuracy

network




To succeed in a high-volume, Print-on-Demand environment, you need simple color control and powerful processing. The ColorPASS-Z70, with an Intel® Pentium® III 700MHz processor, Windows NT® operating system, and in-RIP ICC support, provides a workhorse solution driving the CLC 3100 with precise and brilliant color.

A new PowerWise™ architecture takes print engine speed to the max and features revolutionary ECT Compression with lossless image quality. Photographic-quality color and precise color calibration are assured, thanks to ColorWise® 2, the first color management system open to ICC and custom profiles. There's even a new suite of ColorWise Pro Tools, including Color Editor, Fiery Calibrator™, and ICC Profile Manager, for expert-level accuracy in color matching. Simplified document management ensures a smooth workflow, whether you manage jobs centrally using the Command

WorkStation™ or remotely, using WebTools™ or FieryLink™. The ColorPASS-Z70's wide range of capabilities even includes load balancing, archiving, and media server.

Take advantage of all the productivity-enhancing features like Fiery FreeForm™ variable data printing, and DocBuilder™ Pro's document imposition, which makes booklets, brochures, and calendars as easy as 1, 2, 3! What's more, with NetWise™ 2, you can integrate the ColorPASS-Z70 seamlessly into any network environment, and manage it with ease.

So, if you're in need of high performance, put the extraordinary power of Canon's ColorPASS-Z70 to work for you. And never sweat another deadline.



*ColorPASS-Z70 shown with optional Advanced Controller Interface Kit.


COLORPASS-Z70 SPECIFICATIONS

- Hardware**
 - Canon ColorPASS-Z70 Motherboard
 - Intel Pentium III @ 700MHz CPU
 - 256MB SDRAM
 - 100MHz System Bus
 - 512k level two cache
 - 18.2GB hard disk
 - Internal Zip drive
 - CD-ROM drive
 - CLCs Supported**
 - CLC 3100/1000/2400
 - Document Printing Features**
 - RIP-While-Print®
 - Continuous Print™
 - Reverse order printing
 - Electronic collation
 - Save fast reprint
 - Document full-screen preview, job merging and editing
 - Error-free printing
 - Auto duplexing support
 - Sorting/stapling support*
 - Archiving
 - Load balancing
 - Transparency interleaving
 - Slip-sheeting
 - Media server
 - Networking/Connectivity**
 - Simultaneous auto-switching protocols:
 - EtherTalk, TCP/IP, Novell® IPX™
 - 802.2, 802.3, Ethernet II and SNAP frame types, Novell NDS® compliant
 - Autosensing ports**
 - AUI
 - RJ-45
 - 10/100 Base-T standard support**
 - Optional Token Ring support**
 - Peer-to-peer Windows® printing**
 - Automatic IP configuration**
 - Page Descriptions**
 - Adobe® PostScript® 3
 - Language/Fonts**
 - PDF Printing
 - 136 Adobe Type 1 Roman PostScript scalable fonts
 - Resolution**
 - Continuous-tone at 400 x 400 dpi at all page sizes supported by the copier
 - Scanning**
 - Fiery Scan™ TWAIN-compliant plug-in module for Adobe PhotoShop® (Macintosh® and Windows®)
 - Capable of scanning up to Tabloid at 400 x 400 dpi
 - Utilities**
 - Fiery Link
 - WebTools
 - Fiery Scan
 - Fiery FreeForm
 - Fiery Downloader™
 - Fiery Spooler™
 - Job Log™
 - Fiery Driver™
 - Command WorkStation Software Kit**
 - Color Management ColorWise 2**
 - Color Rendering Dictionaries
 - Photo
 - Presentation
 - Absolute Colorimetric
 - Relative Colorimetric
 - ColorWise Pro Tools
 - Fiery Calibrator—easier calibration
 - Color Editor—customizing curves
 - Profile Manager—supporting ICC profiles
 - Color charts and reference pages
 - RGB separation
 - Spot Color Management—PANTONE®-calibrated
 - Trapping and overprinting
 - Automatic black overprinting
 - Independent RGB, PANTONE® and CMYK controls
 - Pure black text/graphics
 - Accurate Gray Component Replacement (GCR) control
 - Press Simulation**
 - Quick Simulation—adjusts toner density
 - Full Simulation—adjusts toner density and hue
 - Support for SWOP, Euroscale, DIC printing standards and others through ICC profiles
 - Support for custom simulation targets
 - Simulation on a per-job basis
 - Calibration**
 - Default calibration for great out-of-the-box color
 - AutoCal 2
 - Fiery Calibrator
 - Calibration on a per-job basis
 - Memory Management**
 - ECT Compression
 - Optional Hardware/Software**
 - Token Ring Kit
 - Advanced Controller Interface Kit
 - Flat screen monitor
 - Keyboard and mouse
 - DocBuilder Pro
 - Power Supply**
 - Auto-switching 110/220V, 50/60Hz
 - Power Consumption**
 - 120W maximum
 - 400 BTU/hour
 - Dimensions**
 - 21-1/2" x 18-1/2" x 7-1/2" (537.5mm x 462.5mm x 187.5mm)
 - Weight**
 - 55 lb. (24.75kg)
- * Copier must support functionality.

Intel and Pentium are registered trademarks of Intel Corporation. Adobe, PostScript, and PhotoShop are trademarks of Adobe Systems Incorporated. Colorwise and RIP-While-Print are registered trademarks, and Command WorkStation, WebTools, Fiery FreeForm, Fiery Scan, Fiery Downloader, Fiery Spooler, Fiery Calibrator, Job Log, DocBuilder, NetWise, Continuous Print and PowerWise are trademarks of Electronics for Imaging, Inc. Novell and NDS are registered trademarks and IPX is a trademark of Novell, Inc. in the United States and other countries. Windows and Windows NT are registered trademarks of Microsoft Corporation. Macintosh is a registered trademark of Apple Computer, Inc. PANTONE is a registered trademark of Pantone, Inc. Canon and ColorPASS are registered trademarks, and Canon Know How is a trademark of Canon Inc. IMAGEANYWARE is a service mark of Canon U.S.A., Inc. All other terms and product names may be trademarks or registered trademarks of their respective owners and are hereby acknowledged. All specifications are subject to change without notice.

0018W482

1100-CPZ70-50M



Canon KNOW HOW™

73 S Riverside DR, STE 300
Elgin, IL 60120-6425
Phone: 847.760.9282
Fax: 847.760.9281

LANgrafiX

sales@langrafix.net
www.langrafix.com